**THREE STEPS TO PROTECT** 

Knowing what kind of product to buy and when and why to apply it can be a confusing job, so here we have broken it down into three simple steps.



PROTEK

## PREPARE & PRESERVE

#### • Sand, clean & dry

Our products can be applied over the top of old weathered coatings, but for best results apply wood stains to bare timber. Ensure timber is clean & dry.

#### Wood Preserver

If your external timber isn't pressure treated or the preservative chemicals have expired, apply Wood Preserver to protect against rot & fungi.

# • Knotting Agent or Stain Blocking Primer if desired

Apply to prevent resinous knots from staining the coating.



## **COLOUR & PROTECT**

#### Colour

Apply coloured coating to keep the timber looking attractive, create a stunning garden design or fit in with other external timber.

### Protect

The coloured wood stain also creates a protective coating that will weather-proof timber and stop it getting damaged by rain and exposure to the elements.

Use Royal Exterior or Interior, Wood Stain & Protector, Shed & Fence, Stable Coat or Decking Stain to colour and protect.



### **EXTRA PROTECTION**

### Apply Clear Top Coat for extra protection

Use in areas that are subjected to high levels of exposure or to seal a coloured coating where only one coat has been applied for aesthetic purposes. Clear top coats available in Royal, Wood Stain & Protector, Stable Coat & Decking Stain.

## Algaecide/Algae Inhibitor

Apply on top of coatings in areas that are prone to algae growth if desired.

 Varnish (water-based polyurethane breathable products preferable) Apply on top of interior coatings that will be subjected to high levels of wear and tear such as floorboards, table tops and kitchen work surfaces.



Protek, Crowne Trading Estate, Shepton Mallet, Somerset, BA4 5QQ www.protekwoodstain.co.uk Tel: 01749 344697 Email: info@protekproducts.co.uk